

No.1 Sealer

Technical Sheet

No.1 Sealer - hardener, improves adhesion on smooth concrete, on porcelain, vitrified, can be used to primer on plaster, wood, parquet.

No.1 Sealer is a polymeric, ready-to-use and easy to apply product.

USEGE

- As a hardener and sealer of surfaces (plaster, wood or mortar) before receiving thin-film finishes such as ClaudiCemento Fine/Deck,
- As an interface between old walls and new applications.
- As regulator or balancer of absorptions prior to the application of self-leveling products in floors.
- Improves the adhesion between smooth and monolayer concretes.

DILUTION

Ready to be used.

In the case of a very absorbent surface it can be diluted up to 100%.

COVARAGE

- 50 grams / m2 undiluted
- 15 – 25 grams / m2 100% maximum dilution

TOOLS

Roller (foam, wool or fiber), or airless spray gun, brush or brush.

PRODUCT CHARACTERISTICS

Dries in about an hour.

Minimum application temperature: +5 ° C.

Water resistant but allows perspiration to the face.

Retains its properties once cured, between -25 ° C. and 60 ° C.

PACKAGE

5 l.

NOTE: Instructions of use are given based on our testing and knowledge and do not imply any commitment. The responsibility is limited to the value of the used goods.

ClaudiCemento LTD reserves the right, if necessary, to vary any of the information without notice.