

Primer Protector Technical Sheet

The **Protector Primer** is a transparent acrylic polymer compound which should be applied as a layer on top of ClaudiCemento Fine / Deck microcement, before Protector DUR SATIN/MATT is applied.

APPLICATION

It is used as a primer prior to the application of our Protector Dur SATIN/MATT finishing products. It can be applied with a brush, airless gun, roller or sponge pad.

Dilute the product to 100% in 1/1 proportion to avoid glazing effects.

PACKAGING

Supplied in plastic bottles of 5 kgs. (5 liters).

COVERAGE

The consumption of a bottle of 5 liters of Primer Protector is approximately 50 m² in two coats, depending on the porosity and surface texture.

TECHNICAL SPECIFICATIONS

- Has complete adhesion.
- Resistant to water but allows the passage of moisture in the form of vapour
- Retains its properties after polymerisation at temperatures between -25o C and 60o C (-13o F and 140o F)
- resistant to ultraviolet rays.
- Once applied, simple flameless combustion at 250o C (482o F).
- Great resistance to hydrolysis (even in fresh cements).

STORAGE

It is recommended to store the product in a dry and ventilated place with temperatures between 5o C and 35o C .

The material must be used within 6 months of the manufacture date.

Any storage or transportation different from that indicated in this file exempts ClaudiCemento LTD from any type of claim or return of the product